


## MB017 CPF/CKDF Multi-Bay Backplane Module



### INSTALLATION GUIDE



### • Front-panel description



### • Content Description


- Removable Hard Drive Enclosure Rack Kit
- Accessory bag
  - 6#-32 Flat Head screw x 12 pcs
  - 6#-32 Truss Head screw x 12 pcs
  - Miniature key x 2
  - Key x 2 (MB017CKDF only)
- Installation Guide

### • Failure Indicators description

- A. MB017CKDF**
- When housing temperature exceeds the preset temperature setting, the Failure Indicator will indicate Amber color and the alarm buzzer sounds.
  - When fan becomes dysfunctional, the Failure Indicator will indicate Red color and the alarm buzzer sounds.
  - Deactivate the alarm buzzer by pressing the Reset button.
  - The Failure Indicator will still indicate Amber ( or Red ) and will not revert until the failure is properly repaired.
- B. MB017CPF**
- When housing temperature exceeds the preset temperature setting, the Failure Indicator will indicate Red color.
  - The Failure Indicator will still indicate Red and will not revert until the failure is properly repaired.

660028 V2004.09

### • Back-plane description



### • Installing the device

- Unlock the front door by inserting the key provided, turning the key counterclockwise. Pull to open the front door. (Fig.1 - Fig.2 CKDF only)
- Use the miniature key and insert into the key hole to eject handle. (Fig.3)
- Removing the HDD carrier away from the body. (Fig.4a) (Fig.4b)
- Pull the handle outwards to remove the carrier away from the body. Remove the carrier support (Fig.5)
- Secure the HDD to the carrier using the four 6#-32 screws provided. ( Fig.6)
- Inserting the carrier along with HDD into the body. Align the two sides of carrier with the anti-shock rails located at the left and right sides inside the body. (Fig.7a)
- Keep the handle angled from the carrier, then slide the carrier along the anti-shock rails and into the body until fully inserted. (Fig.8a) (Fig.8b)
- Push the handle towards the carrier until it click to completely secure the position of carrier. (Fig.9)
- Close the front door and insert the key into the lock hold to lock. Turning the key clockwise to complete HDD installation. (Fig.10a) (Fig.10b)

**Note :**

- HDD failure will Indicate Red only when signal is inputted by controller. ( please refer to HDD -Fail signal )
- Please terminate the last connector using a terminator
- The above testing results were obtained under the surrounding temp at 25°C.
- Any unrelated changes on the technical specification are subject to change without prior notice.
- We will not be liable responsible for any software - hardware - or other data stored within , or Interfacing with our product which resulted to being damaged / dysfunctional. Cremax will only be responsible to repair / service its own product.
- For any further inquiries about product application or more related product information, please linked to: [www.icydock.com](http://www.icydock.com).